











FA 30 400 18

P. 1 | 2



HS CODE
63079098
CARTON SIZE / PCS.
12 X 8 X 11.5 cm / 12
AET N° 2777/10962-01/E01-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland



REF.	FA 30 400 18
 LG. KG	1.8 m (connector included)
CE	EN 355:2002
MAT.	 30 mm Polyester
	35 mm
	 FA 50 101 17 / FA 50 207 55
	NO
+	VG 11.063
	1.65 KG



**Largeur de l'absorbeur d'énergie**  
 Width of the energy absorber  
**Ancho del absorbedor de energía**  
 Larghezza del assorbitore di energia  
**Breite des Falldämpfers**



**Longueur Poids maxi utilisateur**  
**Length Max. user weight**  
**Longitud Peso máximo del usuario**  
**Lunghezza Peso Max. dell'utente**  
**Länge Höchstgewicht des Benutzers**



**Matière connecteur haut / connecteur bas**  
 Material of top connector / bottom connector  
**Material conector alto / conector bajo**  
 Materiale connettore alto / connettore basso  
**Material oberes / unteres Verbindungselement**



**Ouverture**  
 Gate opening  
**Apertura**  
 Apertura  
**Öffnung**



**Homologué pour le travail à proximité d'arêtes vives**  
 Approved for work near sharp edges  
**Homologado para trabajo cerca de aristas vivas**  
 Omologato per lavoro in prossimità di spigoli vivi  
**Zugelassen für Arbeiten in der Nähe scharfer Kanten**