

FA 60 0006 10/20:

PVC +  STEEL

FA 60 006 10S/20S:

PVC +  INOX

HS CODE

76169990

CARTON SIZE / PCS.

FA 60 006 10/S : 40 x 40 x 24 cm / 25**FA 60 006 20/S** : 40 x 40 x 24 cm / 20





FA 60 006 XX: AET (UE) N°2777/11681-01/E00-00

FA 60 006 XXS: AET (UE) N°2777/10792-02/E01-01

Satra Technology Europe Ltd., N° 2777,
 Bracetown Business Park, Clonee,
 Dublin, D15YN2P, Ireland

MODULE D FI14/14003.02

SGS Fimko Oy, N°0598
 Takomotie 8,
 00380 HELSINKI, Finland

REF.	FA 60 006 10 FA 60 006 20 FA 60 006 10S FA 60 006 20S
CE	EN 795:2012 Type B
	x1
LG.	1.0 m 2.0 m 1.0 m 2.0 m
MAT.	PVC /  STEEL Ø 8.0 mm PVC /  INOX Ø 8.0 mm
R (kN) / MBS (kN)	12 kN / 25 kN
	0.56 kg 0.80 kg 0.46 kg 0.74 kg



Nombre d'utilisateurs
 Number of users
Cantidad de usuarios
 Quantità di utilizzatori
Anzahl der Benutzer

R (kN) / MBS (kN)

Résistance statique (en kN) / Résistance à la rupture
 Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
 Resistenza statica (in kN) / Resistenza alla rottura (in kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)